

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023

**TODECA**

Distribuidores de Productos Químicos

Page 1 of 9  
Print date: 02/06/2023

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Silicone Spray (Industrial)

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **TODECA, S.A.**  
Address: C/ Escoles nº40 Bajos  
City: 43870 - Amposta  
Province: Tarragona (Spain)  
Telephone: 93 454 0828  
E-mail: comercial@todeca.com  
Web: www.todeca.com

**1.4 Emergency telephone number:** 93 454 0828 (Only available during office hours; Monday-Friday; 08:00-18:00)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aerosol 1 : Pressurised container: May burst if heated.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

**Danger**

Hazard statements:

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.

#### 2.3 Other hazards.

The mixture does not contain substances classified as PBT.  
The mixture does not contain substances classified as vPvB.  
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023

Distribuidores de Productos Químicos

Page 2 of 9  
Print date: 02/06/2023

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

#### 3.1 Substances.

Not Applicable.

#### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 649-083-00-0 CAS No: 68512-91-4 EC No: 270-990-9 Registration No: Exempt	[2] Hydrocarbons, C3-4-rich, petroleum distillate, Petroleum gas. (1,3-butadiene < 0.1% w/w)	75 - 100 %	Flam. Gas 1A, H220	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[2] Substance with a national workplace exposure limit (see section 8.1).

### SECTION 4: FIRST AID MEASURES.

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

#### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

No known acute or delayed effects from exposure to the product.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### SECTION 5: FIREFIGHTING MEASURES.

In case of fire, as a general hazard, heat can cause containers to explode.

The product is Extremely flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

#### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023



Distribuidores de Productos Químicos

Page 3 of 9  
Print date: 02/06/2023

### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### **5.2 Special hazards arising from the substance or mixture.**

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.
- Explosions.

### **5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available. Move containers away from the area if there is no danger in doing so. Keep away from containers and continue cooling them from a safe place.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### **6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. Isolate the area and ensure adequate ventilation. Stockpiling in basements, pits or any confined space or depressed area can be hazardous. For exposure control and individual protection measures, see section 8.

### **6.2 Environmental precautions.**

Product not classified as hazardous for the environment, avoid spillage as much as possible.

### **6.3 Methods and material for containment and cleaning up.**

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

### **6.4 Reference to other sections.**

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

## **SECTION 7: HANDLING AND STORAGE.**

### **7.1 Precautions for safe handling.**

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Pressurised gases must be handled by suitably trained and experienced individuals. Use equipment suitable for supply pressure and temperature. Protect containers against physical damage and keep valves clean and in perfect condition. Do not tamper with original packaging.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023

# TODEGA

Distribuidores de Productos Químicos

Page 4 of 9  
Print date: 02/06/2023

### 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. It must not be stored under conditions conducive to corrosion of the container. Protect containers against physical damage and inspect them regularly to ensure they are in good condition.

The product is not affected by Directive 2012/18/EU (SEVESO III).

### 7.3 Specific end use(s).

Silicone Spray (Industrial)

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
Hydrocarbons, C3-4-rich, petroleum distillate, Petroleum gas. (1,3-butadiene < 0.1% w/w)	68512-91-4	United Kingdom [1]	Eight hours	600	1450
			Short term	750	1810

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

### 8.2 Exposure controls.

#### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	100 %				
<b>Uses:</b>	Silicone Spray (Industrial)				
<b>Breathing protection:</b>					
If the recommended technical measures are observed, no individual protection equipment is necessary.					
<b>Hand protection:</b>					
PPE:	Protective gloves against chemicals.				
Characteristics:	«CE» marking, category III.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
<b>Eye protection:</b>					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.				
<b>Skin protection:</b>					
PPE:	Anti-static protective clothing.				
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.				
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023

# TODEGA

Distribuidores de Productos Químicos

Page 5 of 9  
Print date: 02/06/2023

Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance:	The footwear should be checked regularly
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.



### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

#### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Colourless

Odour: Characteristic

Odour threshold: Not applicable (Not relevant for this type of product)

Melting point: Not available

Freezing point: Not available

Boiling point or initial boiling point and boiling range: 32 °C (Estimations in base on the Regulation (CE) N°1272 / 2008 indications.)

Flammability: Not available

Lower explosion limit: Not available

Upper explosion limit: Not available

Flash point: -83 °C (Estimations in base on the Regulation (CE) N°1272 / 2008 indications.)

Auto-ignition temperature: Not available

Decomposition temperature: Not available

pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not applicable (Not relevant for this type of product)

Solubility: Not applicable (Not relevant for this type of product)

Hydrosolubility: Not applicable (Not relevant for this type of product)

Liposolubility: Not applicable (Not relevant for this type of product)

Partition coefficient n-octanol/water (log value): Not available

Vapour pressure: Not available

Absolute density: Not available

Relative density: 0,563 (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Relative vapour density: Not available

Particle characteristics: Not applicable (Not relevant for this type of product)

#### 9.2 Other information

Not applicable/Not available due to the nature/properties of the product

### SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

Extremely flammable aerosol.

Pressurised container: May burst if heated.

#### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023



Distribuidores de Productos Químicos

Page 6 of 9  
Print date: 02/06/2023

- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION.

### 11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

There are no tested data available on the product.

a) acute toxicity;  
Not conclusive data for classification.

b) skin corrosion/irritation;  
Not conclusive data for classification.

c) serious eye damage/irritation;  
Not conclusive data for classification.

d) respiratory or skin sensitisation;  
Not conclusive data for classification.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Not conclusive data for classification.

h) STOT-single exposure;  
Not conclusive data for classification.

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Not conclusive data for classification.

### 11.2 Information on other hazards.

#### Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

#### Other information

There is no information available on other adverse health effects.

## SECTION 12: ECOLOGICAL INFORMATION.

### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023



Distribuidores de Productos Químicos

Page 7 of 9  
Print date: 02/06/2023

No information is available on the degradability of the substances present.  
No information is available about persistence and degradability of the product.

### 12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

### 12.4 Mobility in soil.

No information is available about the mobility in soil.  
The product must not be allowed to go into sewers or waterways.  
Prevent penetration into the ground.

### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS.

### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.  
Follow the provisions of Directive 2008/98/EC regarding waste management.

Waste classification according to the European Waste Catalogue:  
16 WASTES NOT OTHERWISE SPECIFIED IN THE LIST  
16 05 gases in pressure containers and discarded chemicals  
16 05 04 gases in pressure containers (including halons) containing hazardous substances  
Waste classified as hazardous.

Method of treatment according to Directive 2008/98/EC:  
Recovery  
R4 Recycling/reclamation of metals and metal compounds

## SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.  
Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.  
Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.  
Transport document: Airway bill.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1 Date of compilation: 2/06/2023

**TODEGA**

Distribuidores de Productos Químicos

Page 8 of 9  
Print date: 02/06/2023

### 14.1 UN number or ID number.

UN No: UN1950

### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 1950, AEROSOLS, 2.1, (D)

IMDG: UN 1950, AEROSOLS, 2.1 (-83°C)

ICAO/IATA: UN 1950, AEROSOLS, 2.1

### 14.3 Transport hazard class(es).

Class(es): 2

### 14.4 Packing group.

Packing group: Not applicable.

### 14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-D,S-U

### 14.6 Special precautions for user.

Labels: 2.1



Hazard number: Not applicable.

ADR LQ: 1 L

IMDG LQ: 1 L

ICAO LQ: Not applicable.

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Proceed in accordance with point 6.

### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

## SECTION 15: REGULATORY INFORMATION.

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): nwg: Non-hazardous to water. (Autoclassified according to the AwSV Regulations)

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## TODESIL ANTIADHERENTE M / TODESIL LUBRICANTE DE SILICONA MULTIUSOS

Version 1      Date of compilation: 2/06/2023



Distribuidores de Productos Químicos

Page 9 of 9  
Print date: 02/06/2023

### SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H220                      Extremely flammable gas.  
H280                      Contains gas under pressure; may explode if heated.

Classification codes:

Aerosol 1 : Flammable aerosol, Category 1  
Flam. Gas 1A : Flammable gas, Category 1A

#### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
AwSV: Facility Regulations for handling substances that are hazardous for the water.  
CEN: European Committee for Standardization.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.  
WGK: Water hazard classes.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.